

DRIVE BELT SPECIFICATIONS

The chart below lists belts BRP has used the past years with important measurements and specifications.

- Part numbers
- Top Width – measured in/mm
- Thick – measured in/mm
- Angle – both sides combined in degrees
- Circumference – overall outside measurement in/mm
- Type – outside belt design
- Performance – low to high HP
- Durometer – belt rubber compound
- Replace by – designated replacement
- Available – can be ordered through PAC

DRIVE BELT SPECS

Part number	Top width	Thickness	Angle	Circumference	Type	Performance	Durometer	Replace by	Available
414 633 800	34.5	13.5	26	1118	Flat Top	Low	Soft	None	No
414 827 600	33.3	12.7	30	1117.6	Flat Top	Low	Soft	None	Yes
414 860 700	35.3	15.8	25	1105.6	Flat Top	Medium	Medium	None	Yes
415 060 600	35.2	15.3	25	1104.9	Flat Top	Low	Soft	None	Yes
417 300 067	35.6	16.4	24	1113.5	Top Cog	Medium	Medium	None	Yes
417 300 127	36.3	16.4	25	1118	Top Cog	Low	Medium	None	Yes
417 300 128	35.6	16.4	23.5	1101	Top Cog	Medium	Hard	417 300 127	No
417 300 152	35.0	15.5	24	1105	Flat Top	High	Hard	None	No
417 300 155	37.3	14.5	26	1126	Flat Top	Low	Medium	None	Yes
417 300 166	37.7	16.4	26	1118	Top Cog	Medium	Hard	417 300 383	No
417 300 189	38.3	16.7	26	1129	Top Cog	High	Hard	None	Yes
417 300 197	37.6	14.5	26	1106	Top Cog	Low	Medium	None	Yes
417 300 207	37.3	14.5	26	1297	Flat Top	Low	Medium	None	Yes
417 300 230	36.9	15.5	26	1108	Flat Top	NA	NA	None	No
417 300 253	37.7	16.4	24	1118	Top Cog	Medium	Hard	417 300 288	No
417 300 267	37.7	16.7	26	1117	Top Cog	NA	NA	None	No
417 300 287	37.3	14.5	26	1296	Flat Top	High	Hard	None	Yes
417 300 288	37.7	16.7	26	1117	Top Cog	High	Medium	None	Yes
417 300 297	38.2	16.7	25	1112	Top Cog	High	Soft	417 300 288	Yes
417 300 298	33.0	14.4	25	1055	Top Cog	Medium	Medium	417 300 334	No
417 300 299	33.1	14.4	25	1069	Top Cog	Low	Soft	None	No
417 300 326	34.7	15.5	25	1096	Flat Top	Low	Soft	None	Yes
417 300 334	33.0	14.4	25	1069	Top Cog	Medium	Medium	None	Yes
417 300 367	36.7	14.6	25	1095	Flat Top	Low	Soft	None	Yes
417 300 377	38.3	16.7	26	1117	Top Cog	High	Hard	417 300 391	Yes
417 300 383	38.5	16.4	26	1118	Top Cog	Medium	Hard	None	Yes
417 300 391*	38.3	16.7	26	1117	Top Cog	High	Hard	417 300 377	Yes
605 348 425	37.3	14.5	26	1181	Flat Top	Low	Medium	None	Yes

Same as 417 300 377, except glued cord construction